GET /Provenance/{rid}/_history

Retrieves the previous versions of a provenance resource that matches the Resource ID specified in the request.

Sample Request

The following example request retrieves the previous versions of a provenance resource that matches the specified Resource ID:

GET

 $\label{lem:https://test-api.ascension.org/csp/healthshare/hsods/fhir/r4/provenance/{rid}/_history$

Sample Request Body

```
Unset
{
    "rid": "",
    "summary": "true",
    "format": "mime-type",
    "pretty": "true",
    "elements": "",
    "count": "10",
    "since": "0-9",
    "at": "0-9",
    "list": ""
}
```

HTTP request

https://api.ascension.org/csp/healthshare/hsods/fhir/r4/Provenance/{rid}/_history

Path Parameters	
rid (required)	String EXAMPLE
	A unique identifier for a provenance resource (Resource.id).
Query Parameters	
summary (may be empty)	Example
	Unset true
	String EXAMPLE
	The following values are allowed:
	true, text, data, count, false
	A designated subset of a provenance resource.

format (required)	String EXAMPLE
	Specifies the alternative response formats by their MIME-types. If a client is having access issues, the header is accepted.
pretty (may be empty)	Example
	Unset true
	Boolean EXAMPLE
	The following values are allowed:
	true, false

	Requested format for responses from the server. The pretty format ensures that responses are readable by users.
elements (may be empty)	Array EXAMPLE
	any (string) EXAMPLE
	Requests a collection of elements for a provenance resource.
count (may be empty)	Example
	Unset 10
	Number EXAMPLE
	The maximum number of search results that the server can return in a response. The server is not required to return the number of search results requested and is not allowed to return more than the maximum number specified.

since (may be empty)

String EXAMPLE

matches

 $\begin{array}{l} ([0-9] \ ([0-9] \ ([0-9] \ [1-9]) \ [1-9]00) \ | \ [1-9]000) \ (\\ -(0[1-9] \ | \ [0-2]) \ (-(0[1-9] \ | \ [0-9] \ | \ [0-9] \ | \ 3[0-1]) \ (T([01] \ [0-9] \ | \ 2[0-3]) : [0-5] \ [0-9] : ([0-5] \ [0-9] \ | \ 4:00))) ?)?)? \end{array}$

Requests versions of a provenance resource that were created during or after the time specified in the request.

at (may be empty)

String EXAMPLE

matches

 $\begin{array}{l} ([0-9]([0-9]([0-9][1-9]) \mid [1-9]00) \mid [1-9]000) \mid (\\ -(0[1-9] \mid 1[0-2]) \mid (-(0[1-9] \mid [1-2][0-9] \mid 3[0-1]) \mid (T([01] \mid [0-9] \mid 2[0-3]) : [0-5][0-9] : ([0-5][0-9] \mid 60) \mid (\\ (2 \mid (\cdot + \mid -) \mid ((0[0-9] \mid 1[0-3]) : [0-5][0-9] \mid 14 : 00)))?)?)? \end{array}$

Requests versions of a provenance resource that are current during the time specified in the date time value. See the Search notes on date searching for more information.

list (may be empty)

String EXAMPLE

Requests the versions of a provenance resource that are referenced in the list specified in the request.

200: Valid Request

Body application/json